





P+ Digital Back Overview

	P 65+	P 45+	P 30+	P 25+
Description	World's first full frame medium format digital back, featuring Sensor+ with a choice of 60,5 mega pixels for finest resolution or scaled full frame captures for fast workflow and low light versatility.	High resolution shooter with unlimited burst sequences and optimized for large format photography with live preview functionality for easy composition and focus checking.	The top quality fast fashion shooter with ISO 1600, with superior moiré control and well suited for harsh environments.	All-round shooter with unlimited burst sequences and optimized for large format photography with live preview functionality for easy composition and focus checking.
Sensors				
Lens Factor	1.0	1.1	1.3	1.1
CCD size effective (mm)	53.9 x 40.4	49.1 x 36.8	44.2 x 33.1	48.9 x 36.7
Active pixels	8984 x 6732	7216 x 5412	6496 x 4872	5436 x 4080
Pixel size (micron)	Full res. 6 x 6	Sensor+ 12 x 12	6.8 x 6.8	9 x 9
Resolution (mega pixels)	60.5	15.0	39	22
Light sensitivity (ISO)	50-800	200-3200	50-800	100-1600
Exposure time	1/10.000 – 1 minute	1/10.000 sec. up to one hour with XPose+ technology		
Image quality	16bit-OptiColor+, 12 f-stops Dynamic+ and Lens+ technology			
Capture time (frames per second**)	1.0	1.4	0,67	0,8
Battery Lifetime (up to captures/up to stand-by time*)	2000 / 3	2500 / 4	3000 / 4	4000 / 4
Image buffer	1.3 GB High Speed RAM	640 MB high speed RAM		
Display	2.2" QVGA TFT with 230,000 pixels, high brightness and contrast both indoor and outdoor, very fine details			

All testfigures are "expected maximum" made at Phase One test department "all things being equal". Battery used for test is new 2500mAh Li+
 *) standby Time will vary a lot depending on temperature, usage of battery and state of the back e.g. Zero Latency will increase power consumption significantly
 **) Maximum expected performance. The actual performance will be dependent on the camera model and of the camera and digital back capture modes

Your local Phase One partner

www.phaseone.com

P 30+ Camera System



Inset image © Bill Diodato

Expanding the moment of capture

The Phase One P 30+ Camera System is designed to be a seamless extension of your creativity. Extraordinary capture becomes natural through ease of use and direct control.

Shoot digital or film with no lens or back restrictions. Take advantage of the Phase One digital lenses or use your Mamiya 645 AF/AFD or Hasselblad V lenses for an even broader choice.

The fast capture rate and powerful moiré control makes the P 30+ digital back an invaluable tool for high fashion and people photographers. Combine this with 31 mega pixel captures and unfailing performance and you have an incredibly strong partner for any challenge.

In addition, the capacity to shoot at up to 1600 ISO allows you to capture in extremely low light situations.

PHASEONE

what the world's best photography is made of

P 30+ Digital Back Specifications



Inset image © Bill Diodato

- Powerful moiré control
- ISO 100 to 1600 for great versatility
- Up to 48 captures per minute
- 31 mega pixel for large format printing
- XPose+ Technology for long exposures
- Rectangular format sensor 4:3

Imaging technology	
CCD	Less than full frame CCD
Lens Factor	1.3
Resolution	31.6 mega pixels
Active pixels	6496 x 4872 pixels
CCD size effective	44.2 x 33.1 mm
Pixel size	6.8 x 6.8 micron
Image ratio	4:3
Antiblooming	10 f-stops
Dynamic range	12 f-stops
Output files	
Color depth	16 bit per color
Image file formats	TIFF-RGB, TIFF-CMYK, JPEG
Color management	RGB, Embedded ICC profile, CMYK
Sensitivity	
ISO	100, 200, 400, 800, 1600
LCD screen	
Size	2.2"
Resolution	230,400 pixels
Viewing angle	160°
Operating conditions	
Temperature	0° to 40°C (32° to 122°F)
Humidity	15 to 80% RH (non-condensing)
Lighting	
Supports all photographic lights: Flash, tungsten, daylight, fluorescent, HMI	

Computer minimum requirements	
Mac	G4, 1 GB RAM, FireWire® interface, Mac OS X 10.3.9 or later
PC	Pentium III, 1 GB RAM, IEEE 1394 interface, Windows XP/2000
P+ back mounts	
Phase One/Mamiya	Phase One 645 AF, Mamiya 645AFDII/ AFDIII, Mamiya RZ67 PRO IID via adaptor
Phase One H101	Hasselblad H1 and H2
Hasselblad V	Hasselblad 555ELD, 533ELX, 503CW and 501CM Via adaptor: Mamiya RZ67 Pro II Mamiya RB67
Contax 645	Contax 645 AFD
Wide angle & technical cameras	
Possible via the Phase One FlexAdaptor & third party adaptors. Note: Wide angle and large format tilt and swing positions may produce a colorcast in the image	
Storage files	
Phase Ones IIQ RAW file format speeds up the image capture and file transfer. Increases the storage capacity by turning the full 16 bit image data into a compact RAW file format. The default IIQ RAW-large format is completely lossless. IIQ small: 22 MB IIQ large: 35 MB	
Software	
Capture One DB or Capture One Pro	
Certifications	
CE	

645 AF Camera Body Specifications



- Open platform for maximum choice and compatibility
- Ergonomic handling and ease of use
- Use Phase One digital lenses, Mamiya AF lenses or Hasselblad V lenses
- Guaranteed up to 300.000 captures or 3 years (VA)
- Exposures from 1/4000s to 60 minutes
- Prepared for use with leaf shutter lenses

Shutter speed from 1/4000s to 60 minutes, B and X modes can match the extreme long exposure capability of the P+ digital backs or stop action with fast shutter speed or flash.

The mirror and viewfinder of the Phase One 645 camera are almost three times larger than those of 35mm cameras, providing much greater control of focus and composition.

While hosting a complete list of features and custom functions, the Phase One 645 camera is extremely easy to use. All settings important to the exposure are easily controlled by manual dials and soft buttons.

Camera type	Modular 645 AF SLR body
Lenses	Phase One digital and Mamiya 645 AFD Compatible with Hasselblad V lenses Ready for leafshutter lenses
Backs	Digital Back and Film ready Open platform back mount
Auto focus	TTL phase-difference AF with 3 focus points Focus confirmation in manual mode Infrared AF assist for unfailing focus Auto focus lock for swift AF/ M shift
Shutter	1/4000s to 60 minutes Up to 2 FPS Shutter speed bracketing
Flash	Focal plane shutter: Up to 1/125s Leaf shutter lenses: Up to 1/800s' 1st and 2nd curtain flash synchronization X sync terminal and support for TTL flash
Light Metering	TTL metering (average, spot and auto) Programmable AEL button Exposure compensation: +/- 5EV
Mirror-Up	Electronically-activated by switch on grip

Viewfinder	Fixed prism viewfinder Exchangeable diopter from -5 to +3 LCD panel full exposure information
Focusing Screen	Interchangeable focus screens Laser engraved mask for digital back Matte, Grid, Checker, Microprism
Selftimer	Selftimer from 2 to 60 sec
Remote	Screw in cable release on shutter button Terminal for electronic triggering devices
Stop down Preview	Stop down preview button on front of camera
Tripod Socket	1/4 inch and 3/8 inch included
Power Requirements	6 AA batteries (standard or rechargeable) External battery pack - 6 AA batteries External AC adapter
User configuration	3 user presets for capture settings 36 custom settings Customizable dials and buttons
Size	W,H,D // 6,5,7.2" // 153, 128, 184mm
Weight	61oz. / 1730g. w/o batteries